

LOGO-FIX 446

Product Description

High-quality double-sided cloth installation tape for professional requirements. The covered side of the tape is coated with a permanent acrylic adhesive, while the removable adhesive on the open side can be removed from almost all surfaces without leaving any residue. LOGO FIX 446 is solvent-free and has a good resistance to aging and plasticizer.

Technical description	Technical values
Adhesive	Modified Acrylic free of solvent and formaldehyde additives
Carrier	Woven Fabric
Thickness	0,32 mm
Liner	White Silicone Paper (120 g)
Peel Adhesion (on V2A steel after 20 min., 180° peel at 300 mm/min. and 23°)	- removable side > 3 N / 25 mm - permanent > 15 N / 25 mm
Shear Adhesion (25 mm² on V2A steel, 1 kg weight at 23° and 50 % rel. atmospheric humidity)	> 1 Hour
Temperature Range	- 20°C - + 100°C

The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product.

APPLICATION

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

STORAGE & SHELF LIFE

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year.

NOTE

All data above mentioned and technical information given above are typical values, gained from tests we believe to be reliable. Please ensure before using our product that it is suitable for the material for your intended application. For technical assistance please call our product specialists. The data and statements are intended as a source of information, are given without guarantee and do not constitute a warranty. They can vary according to the application conditions. All materials described herein are subject to our conditions of sale.