

LOGO-MOUNT 866 F

Product Description

LOGO MOUNT 866 is a heavy duty mounting tape with a solvent acrylic adhesive. The tape is a real ALLROUNDER and offers an excellent ageing, UV, and chemical resistance against solvents and exterior weathering.

Application

Mounting hooks, mirrors and displays, fixing decorative trims, emblems and holders, mounting in the furniture and automotive industry, exhibition and shop fitting etc.

Technical description	Technical values
Adhesive	Solvent Acrylic
Carrier	White PE-Foam (100 kg/m ³)
Foam Thickness	1,0 mm
Liner	Blue PP Film 100 µm
Peel Adhesion FINAT 1 after 20 Minutes	≥ 10 N / 25 mm
Peel Adhesion FINAT 1 after 24 Hours	≥ 15 N / 25 mm
Holding Power FINAT 8	≥ 500 Hours
Temperature Rang long term short term	- 20°C - + 80°C - 40°C - + 150°C

The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product.

APPLICATION

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

STORAGE & SHELF LIFE

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year.

NOTE

All data above mentioned and technical information given above are typical values, gained from tests we believe to be reliable. Please ensure before using our product that it is suitable for the material for your intended application. For technical assistance please call our product specialists. The data and statements are intended as a source of information, are given without guarantee and do not constitute a warranty. They can vary according to the application conditions. All materials described herein are subject to our conditions of sale.