

# LOGO-TRANS 318

## Product Description

LOGO TRANS 318 is a removable transfer tape for any application where it is necessary that the product is removed from the surface without damaging it. It is used to attach and later remove advertising and promotion materials. Suitable for fixing photos, product and pricing information in presentation folders, e.g. can be replaced with new product collection.

Technical description	Technical values
Adhesive	Removable Acrylic
Carrier	-
Thickness	0,03 mm
Liner	Light Blue Silicone Paper
Peel Adhesion (PSTC 1)	open side 7 +/- 0,5 N / 25 mm closed side 2 +/- 0,5 N / 25 mm
Temperature Range	- 30°C - + 150°C

LOGO TRANS 318 is reverse wound on 1"-core for use with ATG hand dispenser available as follows:

6 mm x 50 mtr. => 144 rolls / carton  
 9 mm x 50 mtr. => 96 rolls / carton  
 12 mm x 50 mtr. => 72 rolls / carton  
 19 mm x 50 mtr. => 48 rolls / carton

The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product.

## APPLICATION

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

## STORAGE & SHELF LIFE

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year.

## NOTE

All data above mentioned and technical information given above are typical values, gained from tests we believe to be reliable. Please ensure before using our product that it is suitable for the material for your intended application. For technical assistance please call our product specialists. The data and statements are intended as a source of information, are given without guarantee and do not constitute a warranty. They can vary according to the application conditions. All materials described herein are subject to our conditions of sale.