























# Pure Acrylic-Tapes



	Product	Adhesive	Carrier	Liner	Thickness mm	Temperature min. (°C)	Temperature max. (°C)	density (kg/m³)	3M ref.
	<b>830</b>	Acrylic	black	Paper, brown	0,25	-30	+150	950	4916
	<b>831</b>	Acrylic	black	PE-Film, red	0,4	-30	+150	900	
	<b>832</b>	Acrylic	black	PE-Film, red	0,6	-30	+150	880	4929
	<b>833</b>	Acrylic	black	PE-Film, red	0,6	-30	+120	890	5925
	<b>834</b>	Acrylic	black	PE-Film, red	1,1	-30	+150	880	4949
	<b>835</b>	Acrylic	black	PE-Film, red	1,1	-30	+120	730	5952
	<b>893</b>	Acrylic	transparent	PE-Film, red	0,25	-30	+180	950	9473
	<b>892</b>	Acrylic	transparent	PE-Film, red	0,5	-30	+180	950	4905
	<b>895T</b>	Acrylic	transparent	PE-Film, trans.	1,0	-30	+180	1000	
	<b>895</b>	Acrylic	transparent	PE-Film, red	1,0	-30	+180	1000	4910
	<b>894</b>	Acrylic	transparent	Paper, brown	1,1	-30	+120	850	
	<b>897</b>	Acrylic	transparent	PE-Film, red	1,5	-30	+180	900	4915
	<b>899</b>	Acrylic	transparent	PE-Film, red	2,0	-30	+180	900	
	<b>896</b>	Acrylic	transparent	PE-Film, red	3,0	-30	+180	900	
	<b>890</b>	Acrylic	darkgrey	PE-Film, red	0,8	-30	+150	820	
	<b>891</b>	Acrylic	darkgrey	PE-Film, red	1,1	-30	+150	820	
	<b>811</b>	Acrylic	grey	PE-Film, white	0,8	-30	+150	820	
	<b>814</b>	Acrylic	grey	PE-Film, red	1,1	-30	+180	730	4211/5385/4611
	<b>812</b>	Acrylic	grey	PE-Film, red	0,8	-30	+150	820	
	<b>884</b>	Acrylic	white	PE-Film, red	0,6	-30	+120	890	4932
	<b>880</b>	Acrylic	white	PE-Film, red	0,8	-30	+150	820	
	<b>881</b>	Acrylic	white	PE-Film, red	1,1	-30	+150	820	4945/4950/4613
	<b>883</b>	Acrylic	white	PE-Film, red	1,1	-30	+180	730	4211/4951
	<b>882</b>	Acrylic	white	PE-Film, red	2,0	-30	+180	730	4912/4955