

LOGO-FIX 442

Product Description

Double-sided tape with a non-tearable cloth carrier coated with an acrylic based adhesive. It ensures a high initial tack and semi-permanent adhesion. LOGO FIX 442 is mostly plasticizer stable, free of solvent and has a very good resistance to aging.

LOGO FIX 442 is ideal for mounting objects for advertising and displays, making moulded rubber parts and profiles self-adhesive and as mounting tape in the printing industry as well as for fixing carpets and PVC flooring for exhibitions and interior decoration.

Technical description	Technical values
Adhesive	Modified Acrylic free of solvent and formaldehyde additives
Carrier	Woven Fabric
Thickness	0,30 mm
Liner	White Silicone Paper
Peel Adhesion (on V2A steel after 20 min., 180° peel at 300 mm/min. and 23°)	> 8 N / 25 mm
Shear Adhesion (25 mm ² on V2A steel, 1 kg weight at 23° and 50 % rel. atmospheric humidity)	> 5 Hours
Temperature Range	- 20°C - + 100°C

APPLICATION

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

STORAGE & SHELF LIFE

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year.

NOTE

All data above mentioned and technical information given above are typical values, gained from tests we believe to be reliable. Please ensure before using our product that it is suitable for the material for your intended application. For technical assistance please call our product specialists. The data and statements are intended as a source of information, are given without guarantee and do not constitute a warranty. They can vary according to the application conditions. All materials described herein are subject to our conditions of sale.